

Secured By Design - Window & Door Specifications

Climatec's REHAU windows and doors can now be specified and ordered to Secured by Design approval, offering customers security and peace of mind.



Our windows and doors have been awarded the Secured by Design certificate and are now recognised as 'Police Preferred Specification' products. This flagship initiative was launched by UK Police to support the principles of "designing out crime" by use of effective crime prevention and security standards for a range of applications.

Our products were assessed by UKAS approved test houses, commissioned to identify technical standards and evaluations which determine the competence of security products and their resistance to criminal attack.

CASEMENT WINDOW SPECIFICATION:

- Classic system
- 52mm Outer Frame
- 75mm Casement T Sash
- Black Gasket
- Internally Beaded
- Frame All Sides Reinforcement
- Maco Shootbolts
- Maxim Handles
- Low-Line Gaskets
- Ogee Beading
- Welded Transoms / Mullions
- Securistyle Hinges c/w Excluder Bolts or Nico Hinges c/w Nico X-tra Bolts
- Top Hung - max height 1250mm, max width 1150mm
- Side Hung - max height 1300mm, max width 700mm

TILT/TURN WINDOW SPECIFICATION:

- Classic system
- 72mm Outer Frame
- 70mm Tilt/Turn Sash
- Black Gasket
- Internally Beaded
- Fully Reinforced
- Low-Line Gaskets
- Ogee Beading
- Winkhaus Topstar Auto Pilot Concealed Gearing or Roto NT Concealed Gearing
- Welded Transoms / Mullions
- Max height 1500mm, max width 900mm

REHAU S706 70MM MULTI-LIGHT CASEMENT WINDOW SYSTEM REHAU S706 70MM PVCU TILT/TURN WINDOW SYSTEM

Successfully tested and certificated to standards as outlined below:-

BS7950: 1997 Specification for enhanced security performance of Casement and Tilt/Turn Windows for domestic applications, supported by BS7412

BM Trada Licence 026/7060 and 031/7060

Certificate No 013



continued over.../



11-14 Fletchers Square, Temple Farm Industrial Estate, Southend-on-Sea, Essex SS2 5RN

Telephone: 01702 613733 Fax: 01702 613367 www.climatec-windows.co.uk

Secured By Design - Window & Door Specifications



VERTICAL SLIDING WINDOW SPECIFICATION:

- Mechanical Cill
- Slim Top Sash
- Intermediate Bottom Sash
- Deep Bottom Rail
- Aluminium Interlocks
- Aluminium Security Bar
- Security Reinforcing
- Security Fitch Catch/Keep
- Security Slide Latches
- Max height 2300mm, max width 1300mm

REHAU HERITAGE VERTICAL SLIDING WINDOW SYSTEM

Successfully tested and certificated to standards as outlined below:-

BS7950: 1997 Specification for enhanced security performance of Vertical Sliding Windows for domestic applications, supported by BS7412

BM Trada Licence 026/7060 and 031/7060

Certificate No 013



SINGLE RESIDENTIAL DOOR SPECIFICATION:

- Classic and Contour system
- Internally Beaded
- Standard Reinforcing
- Security Flag Hinges 3 No
- Fuhr 2 Hook Lock
- Yale Security Cylinder
- Yale Security Handles
- 52mm Bottom O/Frame
- Welded Mid-Rails / Mullions
- Low-Line Gaskets
- Ogee Beading

DOUBLE LEAF DOOR SPECIFICATION:

- Classic and Contour system
- Internally Beaded
- Fully Reinforced
- Security Flag Hinges 3 No
- Mantis 3 French Door Lock
- Yale Paired Security Cylinders
- Yale Security Handles
- 52mm Bottom O/Frame
- Welded Mid-Rails / Mullions
- Low-Line Gaskets
- Ogee Beading
- Millenco Top and Bottom Security Shootbolt Keeps
- Millenco Security One Piece Door Keep

REHAU S706 70MM SINGLE DOOR AND DOUBLE DOOR SYSTEM

Successfully tested and certificated to:-

PAS23-1: 1999 General performance requirements for door assemblies - Single & Double Doorset

PAS24-1: 1999 Enhanced security performance requirements for door assemblies - Single & Double Doorset.

BM Trada Licence 050/7060

Certificate No. 021



Due to our continuous improvement policy, we reserve the right to alter or amend product specifications.