

CALIBRE

Designed and extruded by leading profile supplier REHAU, the Calibre window & door system is a modern, 45° chamfered multi-chambered product and ideal for today's competitive market.

SPECIFICATION

OUTERFRAMES: Choice of 55mm & 67mm chamfered frames.

SASH: 75mm chamfered sash.

GLAZING: Internally beaded for 28mm double glazed units.

GLAZING BEAD: Ogee.

GASKET: Pre-inserted black gaskets.

CASEMENT HARDWARE: Yale friction hinges with high security espag locks. Shootbolt locking is available as an option.

TILT & TURN HARDWARE: Winkhaus Activpilot Tilt before Turn locking gearing.

RESIDENTIAL DOORS: Millenco Mantis high security multipoint lock. All doors hung on 3 no. greenteQ Sigma flag hinges.

FRENCH DOORS: Millenco Mantis high security multipoint lock to master door, profile specific finger bolts to slave door. A passive lock to the slave door is available as an option. All doors hung on 3 no. flag hinges.

CILLS: 95mm, 150mm, 180mm & 225mm.

FRAME EXTENDERS: 20mm & 50mm.

COLOUR OPTIONS: White, Rosewood on White, Oak on White, Anthracite Grey (grained) on White and Black Brown on White as standard. Other foils available on request.

ENERGY RATING: Easily achieves an energy rating of A.

SECURED BY DESIGN: Available on Calbre casement windows.

DOCUMENT Q: Calibre casement windows are Document Q compliant and can therefore be specified for New Build properties,

For any other window specification not shown on this sheet, please enquire about the other window and door systems manufactured by CLIMATEC WINDOWS LTD

