



ORDER FORM - ALUMINIUM RESIDENTIAL DOOR

1-5 Fletchers Square, Temple Farm Ind Estate,
Sutton Road, Southend-on-Sea,
Essex SS2 5RN
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:

Telephone:

Customer Ref:
Date Required:
Previous Quote No:
Works Order No:
Date Received:

Page of

FRAME CONSTRUCTION: Externally Glazed System Internally Glazed System AW604 AW605 AW603 AW608 AW602 AW607 AW622 AW623

FRAME FINISH: White (RAL9910 gloss)* RAL: on White (RAL9910 gloss) RAL: on RAL: *RAL9910 Gloss is our standard White

Opening & Handing / Master	Open In <input type="checkbox"/>	Open Out <input type="checkbox"/>	Left Hung (M) <input type="checkbox"/>	Right Hung (M) <input type="checkbox"/>
Low Threshold	AW604 suitable for 58mm frames only <input type="checkbox"/>		AD100 <input type="checkbox"/>	
Cill Type	None <input type="checkbox"/>	95mm <input type="checkbox"/>	150mm <input type="checkbox"/>	190mm <input type="checkbox"/>
Drainage	Concealed Drain <input type="checkbox"/>		Face Drain <input type="checkbox"/>	None <input type="checkbox"/>
Handle Type & Colour <small>Please see spec sheets on our website for handles styles & colours</small>	STANDARD: <input type="checkbox"/> Handle Type:		Colour:	
	ULTION/SWEET: <input type="checkbox"/> Handle Type:		Colour:	
	CONTEMPORARY: <input type="checkbox"/> Handle Type:		Colour:	
	Other Information:			
Door Lock	Single Door Lock: 2 Hook <input type="checkbox"/>			
	Double Door Lock: 2 Hook + Finger Bolt <input type="checkbox"/> 2 Hook + Passive Lock <input type="checkbox"/>			
Hinges	Four hinges fitted as standard			
Glazing Thickness & Bead Type	28mm <input type="checkbox"/>	32mm <input type="checkbox"/>	Chamfered <input type="checkbox"/>	Square <input type="checkbox"/>
			Black gasket <input type="checkbox"/>	Anthracite Grey gasket <input type="checkbox"/>
Glazing	Unglazed <input type="checkbox"/>	Glass Description:		
	Glazed <input type="checkbox"/>	Spacer Bar Colour*:		
Letter Box	Standard <input type="checkbox"/>	Satin <input type="checkbox"/>		
	Premium <input type="checkbox"/>	White <input type="checkbox"/>	Gold <input type="checkbox"/>	Black <input type="checkbox"/>
Extras	90° Door Restrictor <input type="checkbox"/>		Door Closer (Surface Mounted) <input type="checkbox"/>	
	Split Spindle (Standard to L/Pad Handles) <input type="checkbox"/>			

Overall Frame Size	Width:		Midrail Height: (to centreline)									
	Height:		Sash Width:									
Doc F Slot Vents: Head <input type="checkbox"/> Sash <input type="checkbox"/> Viewed from Outside Please note on drawing if specific location required												
Frame Extenders 20mm Only												
<table border="1"> <tr><td>Top</td><td></td></tr> <tr><td>Bottom</td><td></td></tr> <tr><td>Left</td><td></td></tr> <tr><td>Right</td><td></td></tr> </table>		Top		Bottom		Left		Right		<div style="border: 1px dashed black; width: 100%; height: 100%;"></div>		
Top												
Bottom												
Left												
Right												
Please indicate coupler required. Combination frames not available. 15mm <input type="checkbox"/> 26mm <input type="checkbox"/>												
Special Requirements:												

Ordering Notes:
 Frames will be made using large outerframe unless specified. Please indicate coupler required. Frame sizes & midrail heights should be entered as **overall** including add on's and cills.
Glazing: 28mm glazing as standard / 32mm IGU available
***Spacer Bar:** Black warm edge spacer bar as standard.
Gasket Colour: Black or Anthracite Grey
Cill Height: 25mm **Cill sizes available:** 95 / 150 / 190mm
Frame Add On: 20mm only **Coupler:** 15mm & 26mm available

Important:
 Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed.
 Signed:

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.