

1-5 Fletchers Square, Temple Farm Ind Estate,
Sutton Road, Southend-on-Sea,
Essex SS2 5RN
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:

Telephone:

Customer Ref:

Date Required:

Previous Quote No:

Works Order No:

Date Received:

Secured By Design ☐ Doc Q compliant ☐

U Value Compliant: ☐

BFRC Energy Rated: B ☐

Climatec Certificate & Label required: ☐

Authorised Retailer - Energy Rated Product

AR No: AR B ☐






FRAME CONSTRUCTION - Internally Glazed System (dummy sashes will be required)				GLAZING BEAD / GASKET TYPE	
Outer: AW605 53x58mm <input type="checkbox"/>	AW604 43x58mm <input type="checkbox"/>	Sash: AW685 45mm Flat T Sash	Transom / Mullion: AW632 57mm	Bead: Square	Gasket: Black <input type="checkbox"/> Anthracite Grey <input type="checkbox"/>

FRAME FINISH				HANDLE COLOUR					
White (RAL9910 Std) <input type="checkbox"/>	RAL: <input type="text"/>	RAL: <input type="text"/>	on White <input type="checkbox"/>	White <input type="checkbox"/>	Gold <input type="checkbox"/>	Black <input type="checkbox"/>	Chrome <input type="checkbox"/>	Satin <input type="checkbox"/>	Grey <input type="checkbox"/>

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from **OUTSIDE** – including Tilt & Turn Windows

**Std cill length = frame width +100mm

1	2	3	4	5
				

Special Requirements:

Ordering Notes:

Glazing: 28mm glazing as standard ***Spacer Bar:** Bronze as standard or black if warm edge spacer bar required.

Min/Max Heights: Min Height & Width = 350mm / Max Height = 1500mm, Max Width = 1250mm

Transom/Mullion: AW632 will be used on these windows

Cill Height: 25mm ****Cill sizes available:** 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm only **Coupler:** 15mm & 26mm available

Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :