

1-5 Fletchers Square, Temple Farm Ind Estate,
Sutton Road, Southend-on-Sea,
Essex SS2 5RN
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:	Customer Ref:	Secured By Design <input type="checkbox"/> Doc Q compliant <input type="checkbox"/>
	Date Required:	
	Previous Quote No:	U Value Compliant: <input type="checkbox"/>
	Works Order No:	BFRC Energy Rated: B <input type="checkbox"/>
Telephone:	Date Received:	Authorised Retailer - Energy Rated Product
		AR No: <input type="text" value="AR"/> B <input type="checkbox"/>

FRAME CONSTRUCTION: Internally (dummy sashes will be required) Outer: AW605 53x58mm ☐ AW604 43x58mm ☐ Sash: AW685 45mm Flat T Sash Transom / Mullion: AW632 57mm






FRAME FINISH: White (RAL9910 gloss)* ☐ RAL: on White (RAL9910 gloss) ☐ RAL: on RAL: ☐ *RAL9910 Gloss is our standard White

GLAZING BEAD: Square **GASKET TYPE:** Black ☐ Anthracite Grey ☐

HANDLE COLOUR: White ☐ Gold ☐ Black ☐ Chrome ☐ Satin ☐ Grey ☐ Enduro Steel ☐

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from **OUTSIDE** – including Tilt & Turn Windows **Std cill length = frame width +100mm

1	2	3	4	5
 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>	 Floating Mullion Reqd <input type="checkbox"/>

Special Requirements: 	Ordering Notes: Glazing: 28mm glazing as standard * Spacer Bar: Black warm edge spacer bar as standard. Min/Max Heights: For size limitations see data sheets in the Technical section of our website Transom/Mullion: AW632 will be used on these windows Cill Height: 25mm **Cill sizes available: 95 / 150 / 190mm Locks: Shootbolt locking as standard Frame Add On: 20mm only Coupler: 15mm & 26mm available	Important: Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below. Signed :
--	---	--

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.

Please do not write in the white space around the form. This does not replicate when faxing. Use special requirements box for any further information.