



System	Input Options						Output Data						
	Option 1	Option 2	Option 3	Option 4	Fixed Field (Dependant On Glass Type)	Option 5	Thermal Transmittance	Solar Factor	Window Air Leakage Heat Loss				
Profile Type	Frame	Sash		Glass Type						Label Index	Energy Rating	Report No.	BFRC SEL No.
All Fully Reinforced	Ch = Chambers	Bev = Bevelled TT = Tilt & Turn FS = Fully Sculptured OG = Part Sculptured FR = Fully Reverse	Mullion / Transom	Based on Saint Gobain Products	Unit Centre Pane Value	Spacer Bar Type & Butyl Sealant	U window	G window	L Factor				
Calibre	55mm 5ch	75mm 5ch Bev	67mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Swiss Spacer V	1.4 W/m <sup>2</sup> .K	0.44	0.01 W/m <sup>2</sup> .K	1	A	U13305-1	SEL A Rated 4462
Calibre	55mm 5ch	75mm 5ch Bev	67mm	4mm Planilux / 100% Air / 4mm Total +	1.5 W/m <sup>2</sup> .K	Swiss Spacer V	1.5 W/m <sup>2</sup> .K	0.44	0.01 W/m <sup>2</sup> .K	-10	B	U13305-5	SEL B Rated 4463
Calibre	55mm 5ch	70mm TT	67mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Swiss Spacer V	1.4 W/m <sup>2</sup> .K	0.45	0.01 W/m <sup>2</sup> .K	2	A	U13305-2	SEL A Rated 4462
Calibre	55mm 5ch	70mm TT	67mm	4mm Planilux / 100% Air / 4mm Total +	1.5 W/m <sup>2</sup> .K	Swiss Spacer V	1.6 W/m <sup>2</sup> .K	0.45	0.01 W/m <sup>2</sup> .K	-8	B	U13305-6	SEL B Rated 4463
Calibre	67mm 5ch	75mm 5ch Bev	67mm	4mm Diamant / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Swiss Spacer V	1.4 W/m <sup>2</sup> .K	0.43	0.01 W/m <sup>2</sup> .K	0	A	U13305-3	SEL A Rated 4462
Calibre	67mm 5ch	75mm 5ch Bev	67mm	4mm Planilux / 100% Air / 4mm Total +	1.5 W/m <sup>2</sup> .K	Swiss Spacer V	1.5 W/m <sup>2</sup> .K	0.42	0.01 W/m <sup>2</sup> .K	-14	C	U13305-7	SEL C Rated 4464
Calibre	67mm 5ch	70mm TT	67mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Swiss Spacer V	1.4 W/m <sup>2</sup> .K	0.43	0.01 W/m <sup>2</sup> .K	0	A	U13305-4	SEL A Rated 4462
Calibre	67mm 5ch	70mm TT	67mm	4mm Planilux / 100% Air / 4mm Total +	1.5 W/m <sup>2</sup> .K	Swiss Spacer V	1.5 W/m <sup>2</sup> .K	0.43	0.01 W/m <sup>2</sup> .K	-12	C	U13305-8	SEL C Rated 4464

