



System	Input Options						Output Data						
	Option 1	Option 2	Option 3	Option 4	Fixed Field (Dependant On Glass Type)	Option 5	Thermal Transmittance	Solar Factor	Window Air Leakage Heat Loss	Label Index	Energy Rating	Report No.	BFRC SEL No.
Profile Type	Frame	Sash		Glass Type									
All Fully Reinforced	Ch = Chambers	Bev = Bevelled TT = Tilt & Turn FS = Fully Sculptured OG = Part Sculptured FR = Fully Reverse	Mullion / Transom	Based on Saint Gobain Products	Unit Centre Pane Value	Spacer Bar Type & Butyl Sealant	U window	G window	L Factor				
Dec Flush Sash	55mm 4ch	64mm Flush	70mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Thermobar	1.4 W/m <sup>2</sup> .K	0.46	0.00 W/m <sup>2</sup> .K	7	A	DEC28.533	SEL A Rated 5293
Dec Flush Sash	55mm 4ch	64mm Flush	70mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.7 W/m <sup>2</sup> .K	Thermobar	0.9 W/m <sup>2</sup> .K	0.39	0.00 W/m <sup>2</sup> .K	20	A++	DEC28.541	SEL A Rated 5323
Dec Flush Sash	70mm 3ch	64mm Flush	70mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m <sup>2</sup> .K	Thermobar	1.4 W/m <sup>2</sup> .K	0.43	0.00 W/m <sup>2</sup> .K	0	A	DEC28.573	SEL A Rated 5293

