

ENERGY RATINGS - RESIDENCE COLLECTION



System	Input Options						Output Data						
	Option 1	Option 2	Option 3	Option 4	Fixed Field (Dependant On Glass Type)	Option 5	Thermal Transmittance	Solar Factor	Window Air Leakage Heat Loss	Label Index	Energy Rating	Report No.	BFRC SEL No.
Profile Type	Frame	Sash		Glass Type									
All Fully Reinforced	Ch = Chambers	Bev = Bevelled TT = Tilt & Turn FS = Fully Sculptured OG = Part Sculptured FR = Fully Reverse	Mullion / Transom	Based on Saint Gobain Products	Unit Centre Pane Value	Spacer Bar Type & Butyl Sealant	U window	G window	L Factor				
Residence 7	65mm	66.5mm	73mm	4mm Diamant / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.2 W/m ² .K	0.39	0.01 W/m ² .K	0	A	R9_024	SEL A Rated 6045
Residence 7	65mm	66.5mm	73mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.6 W/m ² .K	Thermobar	0.8 W/m ² .K	0.33	0.01 W/m ² .K	14	A+	R9_027	SEL A Rated 6406
Residence 9	65mm	66.5mm	73mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.2 W/m ² .K	0.38	0.01 W/m ² .K	2	A	R9_016	SEL A Rated 5280
Residence 9	65mm	66.5mm	73mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.6 W/m ² .K	Thermobar	0.8 W/m ² .K	0.33	0.01 W/m ² .K	15	A+	R9_015	SEL A Rated 5320

